HIDDEN CAMERA Sends Audio/Video Signal Wirelessly

The 2.4GHz Mini Video Watcher and Spy Cam are perfect for monitoring minors in the next room. And It can be install in the living room, family room and bedroom* (Please check with your local law enforcement. Some state prohibit Audio and Video recording at the same time.) A/V signals can be transmitted wirelessly up to 50 meters.

Soft and Huggable Bear with built-in Hidden Camera in one of its eye. Great for display in the living room, family room, and bedroom.
SPY-BVC-8 Huggable Bear Hidden Camera $95.00

Elegant Working Clock with Hidden Camera built-in in the clock.Great for display in the living room, family room, and bedroom.
SPY-CVC-8 Working Clock Hidden Camera $95.00

SPY CAMERA (SMALLER THAN THE SIZE OF AA BATTERY)

1/4" Color CMOS Camera
Pixel :250K(NTSC)
Resolution : Horizontal 380 TV Lines
Shutter Speed :1/50-1/63000 Sec.
Min. Illumination :1.5Lux/ F1.2
S/N Ratio : 48dB. AGC : +18dB
Power Supply : DC 9 -12V
Power consum. : 35 mA(Max)
Dimension :12(W)X12(D)
Net Weight : 10 g

NEW!

Power Adapter sold separately.
Battery not included for demo only

SPY-508 Spy Camera $65.00

MINI WIRELESS CAMERA

Camera, Receiver, cable & power adapters Everything you need in one package!

WRCAM-809

10mW mini color wireless camera (pinhole)
- Frequency: 2.4GHz
- Size: **22x22x40mm**
- Resolution ratio: 380 lines • Illumination: 1.5 lux
- Output standard: PAL/NTSC
- Transmission distance: 80-150m

Includes battery and Cable, bracket, wireless camera, receiver, power adapters for camera & receiver
WRCAM-809 Mini wireless camera kit $99.00

ULTRA MINI WIRELESS CAMERA

The Camera is about the size of 9v battery. Perfect toplace anywhere at home formonitoring nanny & kids

NEW!

WRCAM-811

10mW ultra-mini color wireless camera (pinhole)
- Frequency: 2.4GHz
- Size: **22x22x24mm**
- Resolution ratio: 380 lines • Illumination: 1.5 lux
- Output standard: PAL/NTSC
- Transmission distance: 80-150m

Includes battery and Cable, wireless camera, receiver, power adapters for camera & receiver
WRCAM-811 Ultra-mini wireless camera kit $95.00

WIRELESS CAMERA

WRCAM-1502-100

WIRELESS HIDDEN CAMERA

WRCAM-1503-100

- Simple to Use - Just plug in the power, no other cabling required.
- Color wireless surveillance system, accessible up to 8 camera simulteously
- Good for indoor or outdoor use (transmission range up to 200 meters)
- 10mW (dipole antenna inside) 100mW (directional-adjustable patch antenna)

WIRELESS CAMERA KIT includes
a. 2.4GHz Wireless Camera
b. Onmi-directional Bracket
c. Power Adapter x 2 (6VDC, 9VDC)
d. 2.4 Ghz A/V receiver with patch-antenna
e. Audio/Video Connecting Cable
f. IR remote controller
g. User's manual

- 2:1 interlace scanning system wireless camera
- 380TV Lines on the resolution
- Internal Synchronize
- 3 Lux minimum Illumination

AGC: On(preset); ELC: On(preset); ATW(preset)
WRCAM-1502-10 10mA (dipole) $99.00

WIRELESS SPY CAMERA KIT includes
a. 1/4" CMOS camera x 1
b. Mini transmitter with microphone x 1
c. Battery pack for the camera x 1
d. Digit-display 2.4 GHz A/V Receiver
e. Audio/Video Connecting Cable
f. IR Remote controller
g. 9VDC Power adapter x 1
h. User's manual x 1

- 380TV Lines on the resolution
- Internal Synchronize
- 3 Lux minimum Illumination

AGC: On(preset); ELC: On(preset); ATW(preset)
WRCAM-1503-10 10mA 26x21.7mm $99.00

PIPF-24100

PIPS-9DC300

Model #	Voltage	Milliamps	Plug Terminations	
PIPS-9DC300	9 Volt DC	300MA	2.1 MM COAX	$2.30
PIPS-9DC500-25	9 Volt DC	500MA	2.5 MM COAX	$2.50
PIPS-12DC300	12 Volt DC	300MA	2.1 MM COAX	$2.50
PIPS-12DC500-B	12 Volt DC	500MA	2.1 MM COAX	$2.50
PIPS-12DC500-25	12 Volt DC	500MA	2.5 MM COAX	$2.30
PIPS-12DC500-W	12 Volt DC	500MA	2.1 MM COAX	$2.50
PIPS-12500R	12 Volt DC	500MA	Fully Regulated	$3.75
PIPS-121AR	12 Volt DC	1 AMP	Fully Regulated	$6.50
PIPF-24100	24 Volt DC	4 AMP	open frame	$18.00
PIPF-28100	28 Volt DC	2.5AMP	open frame	$18.00
PIPS-241000	24 Volt DC	1 AMP	screw terminal	$6.50

PIPS-241000

PIAD-2410

Model #	Voltage	VA	
PIAD-1220	12 Volt AC	20 VA	$2.95
PIAD-1240	12 Volt AC	40 VA	$3.60
PIAD-1620	16 Volt AC	20 VA	$2.95
PIAD-1640	16 Volt AC	40 VA	$3.60
PIAD-1640P	16.5V AC; 40 VA, PTC auto reset		$4.95
PIAD-2410	24 Volt AC	10 VA	$2.50
PIAD-2420	24 Volt AC	20 VA	$2.95
PIAD-2440	24 Volt AC	40 VA	$3.60
PIAD-2450	24 Volt AC	50 VA	$5.95

PIAD-AC24

PIAD-2420CA

PIAD-2420CA AC to AC 24V 2A/42VA $3.60
PIAD-AC24 24VAC to 12VDC, 500mA $4.50

AVC-PA12V Regulated

Power adapter for Cameras AC120V/DC12V 500mA
AVC-PA12V $ 6.00

Min Tripod - Antenna Type
TRIPOD $ 4.99

PIDB-12VDC-9

PIDB-24VAC-9

PIDB-12VDC-18

PIDB-24VAC-18

PIDB-1224-18

PIDB-1224-ACDC

DC POWER DISTRIBUTION BOX
- 12 Volt DC 110V switching power supply
- 4 Amp continuous current
- 9 individually fused output with LED indicators for each fuse
- Measures 9 3/4" L x 3 3/4" D x 8 1/8" W

PIDB-12VDC-9 12 VDC for 9 cameras $35.00
PIDB-12VDC-18 12 VDC for 18 cameras $50.00

AC POWER DISTRIBUTION BOX
- 24 Volt AC transformer
- 4 Amp continuous current
- Individually fused output with LED indicators for each fuse
- Measures 9 3/4" L x 3 3/4" D x 8 1/8" W

PIDB-24VAC-9 24 VAC for 9 cameras $35.00
PIDB-24VAC-18 24 VAC for 18 cameras $50.00

AC/DC COMBO POWER DISTRIBUTION BOX
- 9 port 24 Volt AC transformer and 9 port 12 Volt Switching Power.
- Individually fused output with LED indicators for each fuse
- Measures 9 3/4" L x 3 3/4" D x 8 1/8" W

PIDB-1224-18 12VDC x 9 & 24VAC x 9 $53.00

AC/DC POWER DISTRIBUTION BOX
- 12 Volt DC or 24 Volt AC (power adapter not included)
- 9 camera distribution power supply
- Plastic White Housing
- use 12VDC or 24VAC; note: do not combine.

PIDB-1224-ACDC 12/24V AC/DC for 9 camera $20.00
PIAD-2460 24 Volt AC, 60 VA Power Adapter $7.00
PIPS-1236 12 Volt DC 3.6 AMP Power Adapter $7.50